

JINXUSOLU OBD-II converter and bluetooth chips comparison table

	MIC1103	MIC3611	MIC3612	MIC3613	MIC3X2X	MIC33LT	MIC34LE	MIC64LT	MIC65LE	MIC66LE
SAE J1850-PWM	●	●	●	●	●					
SAE J1850-VPW	●	●	●	●	●					
ISO 9141-2	●	●	●	●	●					
ISO 14230-4(slow)	●	●	●	●	●					
ISO 14230-4(fast)	●	●	●	●	●					
ISO 15765-4(CAN J1962 PIN 6/14)	●	●	●	●	●					
SAE J1939(CAN J1962 PIN 6/14)	●	●	●	●	●					
ISO 11898(raw CAN J1962 PIN 6/14)	●	●	●	●	●					
Single Wire CAN(GMLAN J1962 PIN1)				●	●					
Medium Speed CAN(MS-CAN J1962 PIN 3/11)			●	●	●					
Infotainment CAN(J1962 PIN 1/8)					●					
Fiat High Speed or Fault-Tolerant CAN(J1962					●					
GM High-Speed (J1962 PIN 12/13)					●					
FEPS Voltage					●					
Bluetooth ER/BDR						●	●	●	●	●
Bluetooth BLE							●		●	●
Support MFI										●
Wake up wirelessly							●	●	●	●
Auto sleep mode	●	●	●	●	●					
Button Wake up device		●	●	●	●					
OBD bus activity wake up		●	●	●	●					
Battery voltage drop wake up		●	●	●	●					
Compatibility with the ELM327 instruction	v2.3	v2.3	v2.3	v2.3	v2.3					
Compatibility with the ELM329 instruction		v2.2	v2.2	v2.2	v2.2					
Compatibility with the STN instruction			●	●	●					
Support VT instruction		●	●	●	●					
Free firmware updates	●	●	●	●	●					
Maximum number of OBD bytes sent	8	1023	1023	1023	4095					
Maximum number of bytes sent						600	600	16384	16384	16384
Buy >= 10 pcs Currency: USD	\$5.0	\$7	\$7.5	\$8	\$11	\$1.4	\$2.1	\$5.0	\$6.7	\$8
Buy >= 100pcs Currency: USD	\$4.5	\$6.5	\$7.0	\$7.5	\$9.7	\$1.2	\$1.8	\$4.5	\$5.8	\$6.9
Buy >= 1000pcs Currency: USD	\$3.5	\$5.5	\$6.0	\$6.5	\$8.5	\$0.8	\$1.5	\$4	\$5	\$6